

**ELECTRO-MECHANICAL SURGICAL DEVICE**

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation-in-part of U.S. Patent Application Serial No. 09/723,715, filed on November 28, 2000, <sup>PAT 6,793,652</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,451, filed on June 2, 1999, <sup>PAT 6,315,184</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/324,452, filed on June 2, 1999, <sup>PAT 6,443,973</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/351,534, filed on July 12, 1999, <sup>PAT 6,264,087</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/510,923, filed on February 22, 2000, <sup>PAT 6,517,565</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,452, <sup>PAT 6,443,973</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/510,927, filed on February 22, 2000, <sup>PAT 6,716,233</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,452, <sup>PAT 6,443,973</sup> and a continuation-in-part of U.S. Patent Application Serial No. 09/510,932, filed on February 22, 2000.

FIELD OF THE INVENTION

The present invention relates to an electro-mechanical surgical device.

BACKGROUND INFORMATION

The literature is replete with descriptions of surgical devices. For example, U.S. Patent No. 4,705,038 to Sjostrom et al. describes a surgical system for powered instruments. The system includes a handpiece containing a motor and including a recess adapted to receive one of a plurality of surgical devices. A pair of reed switches is disposed within the recess, and each of the surgical devices includes one or two magnets adapted to actuate the reed switches in a particular

*md*  
*03/10/05*

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100

**ELECTRO-MECHANICAL SURGICAL DEVICE**

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation-in-part of U.S. Patent Application Serial No.

5

09/723,715, filed on November 28, 2000,<sup>PAT 6,793,652</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,451, filed on June 2, 1999,<sup>PAT 6,315,184</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/324,452, filed on June 2, 1999,<sup>PAT 6,443,973</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/351,534, filed on July 12, 1999,<sup>PAT 6,264,087</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/510,923, filed on February 22, 2000,<sup>PAT 6,517,565</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,452,<sup>PAT 6,443,973</sup> a continuation-in-part of U.S. Patent Application Serial No. 09/510,927, filed on February 22, 2000,<sup>PAT 6,716,233</sup> which is a continuation-in-part of U.S. Patent Application Serial No. 09/324,452,<sup>PAT 6,443,973</sup> and a continuation-in-part of U.S. Patent Application Serial No. 09/510,932, filed on February 22, 2000.

FIELD OF THE INVENTION

The present invention relates to an electro-mechanical surgical device.

20

BACKGROUND INFORMATION

The literature is replete with descriptions of surgical devices. For example, U.S. Patent No. 4,705,038 to Sjoström et al. describes a surgical system for powered instruments. The system includes a handpiece containing a motor and including a recess adapted to receive one of a plurality of surgical devices. A pair of reed switches is disposed within the recess, and each of the surgical devices includes one or two magnets adapted to actuate the reed switches in a particular

25

*ML*  
*03/10/05*

10  
09836781-041704  
15